

ENVIRONMENTAL PROTECTION AGENCY



Mary A. Gade, Director 217/782-0610

2200 Churchill Road, Springfield, IL 62794-9276

April 3, 1997

MAJOR

U. S. Environmental Protection Agency
 Attention: 5WN - 16J Eugene Chaiken, Chief
 NPDES Support and Technical Assistance Branch
 Region V
 77 West Jackson Boulevard
 Chicago, Illinois 60604

Re: Commonwealth Edison Company Crawford Generating Station NPDES Permit No. IL0002186 Draft Permit Notification

Gentlemen:

In accordance with our agreement, we hereby submit a Draft Permit and Public Notice/Fact Sheet for the above subject discharger. The IEPA understands that this Draft Permit will not be reviewed by the Region at this time.

Should this understanding be incorrect, any verbal comments can be directed to Beth Unser at the indicated telephone number.

Very truly yours,

Stephen F. Nightingale, P.E.

Manager, Industrial Unit, Permit Section Division of Water Pollution Control

Division of Water Pollution Contro

SFN:BAU\96111903.PSJ

Attachments: Draft Permit, Public Notice/Fact Sheet, Additional Backup Material

cc: Records Unit

NPDES Permit No. IL0002186 Notice No. BAU\96111903.PSJ Date: APR 1 1 1997

National Pollutant Discharge Elimination System (NPDES) Permit Program

PUBLIC NOTICE/FACT SHEET Draft Modified NPDES Permit to Discharge into Waters of the State

Public Notice/Fact Sheet Issued By:

Illinois EPA Division of Water Pollution Control Permit Section 2200 Churchill Road Springfield, Illinois 62706 217/782-0610

Name and Address of Discharger:

Commonwealth Edison Company **Environmental Services Department** Post Office Box 767, 35 FNW Chicago, Illinois 60690

Name and Address of Facility:

Commonwealth Edison Company Crawford Generating Station 3501 South Pulaski Chicago, Illinois 60623 (Cook County)

The Illinois Environmental Protection Agency (IEPA) has made a tentative determination to modify an NPDES permit to discharge into the waters of the state and has prepared a draft permit for the above named discharger.

Length of Permit: Name of Receiving Waters: Classification of Receiving Waters:

Approximately 3 Years Chicago Sanitary and Ship Canal

Secondary Contact and Indigenous Aquatic Life Water

The following water quality and effluent standards and limitations were applied to the discharge:

Except as otherwise noted the effluent concentrations and load limitations (including toxics) were based on effluent and, if applicable, water quality limitations specified in Illinois Pollution Control Board (IPCB), Rules and Regulations, Subtitle C: Water Pollution and/or 40 CFR 423.

The applicant operates Crawford Generating Station which is a fossil fueled steam electric generating facility with a net generating capacity of 702 MW (SIC 4911). Coal, gas and oil are the fossil fuels used. Operational Units #7 and #8 are pulverized coal-fired furnaces. Unit #6 which has six gas-fired boilers is retired on site. Twelve jet turbine peaking units which use gas or oil are operational on site. The Chicago Sanitary and Ship Canal provides Condenser Cooling and House Service Water for station operations. Chicago municipal water is the source supplying the station potable, sanitary and boiler feed water supply systems.

Regulated discharges from Crawford Generating Station to the Chicago Sanitary and Ship Canal are: No. 001 Condenser Cooling Water and House Service Water with an average flow of 414.5 MGD; No. 001(a) Demineralizer Regenerant Wastes with an average flow of 0.035 MGD; No. 001(b) Unit #7 and #8 Boiler Blowdown with an average flow of 0.055 MGD; No. 001(c) Recirculating Wastewater Treatment System Blowdown with an average flow of 1.05 MGD, No. 001(d) Intake Screen Backwash with an intermittent flow, and No. 002 area 14 runoff (boiler room area) with an intermittent flow.

The following modification is proposed:

The bottom ash hydrobin system that currently drains into Pit #13 will be relocated inland and discharge into Pit #16. Pit #13 will be taken out of service.

Flow will be monitored. The primary parameters to be monitored and limited are pH, total suspended solids, oil and grease, total residual chlorine, total residual oxidant, iron, copper, and temperature.

Application is made for the existing discharges which are located in Cook County, Illinois at latitude 41° 49' 35" and longitude 87° 43' 24".

Public Notice/Fact Sheet -- Page 2 -- NPDES Permit No. IL0002186

Monitoring frequencies and reporting requirements were established by using the authority set forth in IPCB, Subtitle C: Water Pollution and/or Subtitle D, Mine Related Water Pollution, Title 40, Section 122.48 and 122.44(i) of the Federal Regulations, and/or using the authority provided in Section 402(a)(1) of the Clean Water Act.

Load limitations were calculated as follows:

- (A) Average or Maximum Flow (MGD) X Concentration Limit (mg/l) X 8.34 = lbs/day; and/or
- (B) Average Monthly Production or Daily Production X Effluent Limitation from Federal Regulations = lbs/day.

Interested persons are invited to submit written comments on the draft modified permit to the IEPA at the above address. The NPDES permit and notice number(s) must appear on each comment page. Any interested person may submit a written request for a public hearing on the draft permit, stating his or her name and address, the nature of the issues proposed to be raised and the evidence proposed to be presented with regards to those issues.

The application, engineer's review notes including load limit calculations, Public Notice/Fact Sheet, draft modified permit, comments received, and other documents are available for inspection and may be copied at the IEPA between 9:30 a.m. and 3:30 p.m. Monday through Friday.

All comments on the draft modified permit and requests for hearing must be received by the IEPA not later than 30 days from the date of this publication. If written comments or requests indicate a significant degree of public interest in the draft modified permit, the permitting authority may, at its discretion, hold a public hearing. Public notice will be given 30 days before any public hearing. For further information call the Public Notice Clerk at 217/782-0610.

Illinois Environmental Protection Agency

APR 1 1 1997

DRAFT

PUBLIC NOTICED

Division of Water Pollution Control

2200 Churchill Road

Springfield, Illinois 62706

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM

Modified (NPDES) Permit

Expiration Date: April 1, 2000

Issue Date: April 26, 1995 Effective Date: April 26, 1995 Modification Date:

Name and Address of Permittee:

Commonwealth Edison Company Environmental Services Department Post Office Box 767, 35 FNW Chicago, Illinois 60690

Discharge Number and Name:

001 Condenser Cooling Water and House Service Water

001(a) Demineralizer Regenerant Wastes

001(b) Unit #7 and #8 Boiler Blowdown

and Boiler Drain

001(c) Recirculating Wastewater Treatment System Blowdown

001(d) Intake Screen Backwash

002

Area 14 Runoff (Boiler Room Area)

Facility Name and Address:

Commonwealth Edison Company Crawford Generating Station 3501 South Pulaski Chicago, Illinois 60623 (Cook County)

Receiving Waters

Chicago Sanitary and Ship Canal

In compliance with the provisions of the Illinois Environmental Protection Act, Subtitle C Rules and Regulations of the Illinois Pollution Control Board, and the FWPCA, the above-named permittee is hereby authorized to discharge at the above location to the above-named receiving stream in accordance with the standard conditions and attachments herein.

Permittee is not authorized to discharge after the above expiration date. In order to receive authorization to discharge beyond the expiration date, the permittee shall submit the proper application as required by the Illinois Environmental Protection Agency (IEPA) not later than 180 days prior to the expiration date.

Thomas G. McSwiggin, P.E. Manager, Permit Section Division of Water Pollution Control

Effluent Limitations and Monitoring

LOAD LIMITS

CONCENTRATION

lbs/day

LIMITS mg/l

DAILY

SAMPLE

SAMPLE

PARAMETER

30 DAY DAILY AVG. MAX. 30 DAY AVG.

MAX.

FREQUENCY

TYPE

1. From the effective date of this permit until the expiration date, the effluent of the following discharge(s) shall be monitored and limited at all times as follows:

Outfall(s): 001 Condenser Cooling Water and House Service Water***

This discharge consis	sts of:		31	Approximate F	Flow
 Condenser Cooling House Service Wa Demineralizer Reg Boiler Blowdown Boiler Drain Recirculating Was Intake Screen Bac 	ater generant Wastes tewater Treatment System Blowdown			9.0 MGD 9.0 MGD 0.035 MGI 0.055 MGI Intermitter 1.05 MGD Intermitter	D nt
Flow (MGD)**				Daily	Continuous
Total Residual		0.2		1/Week	*Concentra-
Chlorine/Total Residu	ral Oxidant*				tion Curve
Temperature	See Special Conditions 3, 4 and 5			Daily	Continuous

^{*}See Special Conditions 6 and 15.

^{**}Shall be reported as a monthly average and daily maximum.

^{***}See Special Condition 16.

DRAFT

Effluent Limitations and Monitoring

APR 1 1 1997

LOAD LIMITS

CONCENTRATION

PUBLIC NOTICED.

lbs/day 30 DAY

DAILY

MAX.

LIMITS mg/l DAILY 30 DAY

SAMPLE

SAMPLE

PARAMETER

AVG.

AVG.

MAX.

FREQUENCY

TYPE

1. From the effective date of this permit until the expiration date, the effluent of the following discharge(s) shall be monitored and limited at all times as follows:

Outfall(s): 001(a) Demineralizer Regenerant Wastes

This discharge consists of:

Approximate Flow

1. Demineralizer Regenerant Wastes

0.035 MGD

Continuous Flow (MGD)** Daily Grab* Total Suspended Solids 15.0 30.0 1/Month 15.0 20.0 1/Year Grab Oil and Grease

^{*}Sample type shall be 8-hour composite if the equalization tank is bypassed for maintenance purposes.

^{**}Shall be reported as a monthly average and daily maximum.

Effluent Limitations and Monitoring

	LOAD L		CONCENT	3 20 7 7 7 70 70 70		
and the second second	30 DAY	DAILY	30 DAY	DAILY	SAMPLE	SAMPLE
PARAMETER	AVG.	MAX.	AVG.	MAX.	FREQUENCY	TYPE

1. From the effective date of this permit until the expiration date, the effluent of the following discharge(s) shall be monitored and limited at all times as follows:

Outfall(s): 001(b) Unit #7 and #8 Boiler Blowdown and Boiler Drain

This Discharge Consists of:				Approx	imate Flow	
Boiler Blowdown Boiler Drain				O. Ir		
Flow (MGD)*	v n				Daily	Continuous
Total Suspended Solids			15.0	30.0	1/Month	8-hour Composite
Oil and Grease			15.0	20.0	1/Year	Grab

^{*}Shall be reported as a monthly average and daily maximum.

DRAFT

Effluent Limitations and Monitoring

APR 1 1 1997

LOAD LIMITS lbs/day

CONCENTRATION LIMITS mg/l

PUBLIC NOTICED

30 DAY

DAILY MAX.

30 DAY DAILY

SAMPLE

SAMPLE

PARAMETER

AVG.

AVG.

MAX.

FREQUENCY

TYPE

Outfall(s): 001(c) Recirculating Wastewater Treatment System Blowdown***

This discharge consists of:

Approximate Flow

Ash sluice water Ash hopper overflow 3. Coal pile runoff Non-Chemical metal cleaning wastes 5. Demineralizer filter backwash

6. Boiler and turbine building floor drains 7. Fuel oil handling area runoff

8. Unit #7 air compressor cooling water 9. Coal storage area #2 runoff 10. Settling basin area #3 runoff

11. Ash pile area #18 runoff 12. Yard drainage area #15 13. Ash hopper area #16

14. South detention basin consisting of area runoff from:

a. Transmission terminal areas #5, 6 and 12

b. Transformer area #7

c. Oil storage areas #8 and 9 d. Power block area #11

e. Dock conveyor area #22

0.5 MGD 0.25 MGD Intermittent Intermittent 0.01 MGD 0.03 MGD Intermittent 0.14 MGD Intermittent Intermittent Intermittent Intermittent Intermittent Intermittent

Flow (MGD)*			Daily	Continuous
pH See	Special Condition 1		1/Week	Grab
Total Suspended Solids	15.0	30.0	1/Week	24 Hour Composite
Oil and Grease	15.0	20.0	1/Week	Grab
Iron	1.0	1.0	1/Month**	24 Hour Composite
Copper	0.5	1.0	1/Month**	24 Hour Composite

^{*}Shall be reported as a monthly average and daily maximum.

^{1.} From the effective date of this permit until the expiration date, the effluent of the following discharge(s) shall be monitored and limited at all times as follows:

^{**}The sampling frequency for total iron and total copper shall be daily during discharge of non-chemical metal cleaning wastes. At all other times the sampling frequency shall be once per month.

^{***}See Special Condition 16.

Special Conditions

SPECIAL CONDITION 1. The pH shall be in the range 6.0 to 9.0.

<u>SPECIAL CONDITION 2</u>. Samples taken in compliance with the effluent monitoring requirements shall be taken at a point representative of the discharge, but prior to entry into the receiving stream.

SPECIAL CONDITION 3. The receiving waters are designated as Secondary Contact and Indigenous Aquatic Life Waters by Section 302.408, Illinois Administration Code, Title 35, Chapter 1, Subtitle C, as amended. These waters shall meet the following standard:

Temperatures shall not exceed 93°F (34°C) more than 5% of the time, or 100°F (37.8°C) at any time at the edge of the mixing zone which is defined by Rule 302.102 of the above regulations.

SPECIAL CONDITION 4. In lieu of the requirements of Section 302.211(d) and (e), Illinois Administrative Code, Title 35, Subtitle C, as amended, effluent shall not alone or in combination with other sources cause temperatures in the main channel of the Lower Des Plaines River at the I-55 Bridge to exceed the temperatures set forth in the following table, except in accordance with the allowable monthly excursions detailed below:

	<u>Jan</u>	<u>Feb</u>	<u>Mar</u>		<u>Apr</u> 16-30		<u>May</u> 16-30			<u>July</u>	Aug	Sept	<u>Oct</u>	Nov	Dec
°F	60	60	65	73	80	85	. 90	90	91	91	91	90	85	75	65

These standards may be exceeded by no more than 3°F during 2% of the hours in the 12-month period ending December 31, except that at no time shall ComEd's plants cause the water temperature at the I-55 Bridge to exceed 93°F. (ComEd's plants continue to be subject to the Secondary Contact Standards at the point of discharge).

SPECIAL CONDITION 5. Permittee shall comply with all temperature limitations as imposed by the Pollution Control Board's order in AS 96-10, dated October 3, 1996.

SPECIAL CONDITION 6. Total residual oxidant shall not be discharged from any single generating unit for more than two hours per day. The daily mean concentration of total residual oxidant shall be based on a concentration curve. The concentration curve shall be generated using grab samples with a sampling frequency of five minutes or less over the exposure time. The exposure time is defined to be from the point of first detectable measurement to the point of the last detectable measurement of total residual oxidant. Concentration curves shall be submitted with Discharge Monitoring Reports. The frequency and duration of the oxidant dosing period plus the amount of chlorine or bromine applied shall be reported on the Discharge Monitoring Reports. For reporting purposes, the daily discharge shall be the average of all non-zero values measured in a day and the monthly average shall be the average of all daily discharges. Discharge Monitoring Reports shall indicate whether chlorine or bromine compounds were used during the month.

For the purpose of determining compliance, the highest single instantaneous TRC/TRO concentration measured during compliance curve sampling on any day will be regarded as the daily maximum concentration. Total residual oxidant concentration shall be measured and reported in terms of total residual chlorine.

SPECIAL CONDITION 7. This facility has the following discharges of storm water associated with industrial activity:

The east oil water separator and switch house building roof drains, which discharge to the Chicago municipal combined sewer system.

SPECIAL CONDITION 8. There shall be no discharge of polychlorinated biphenyl compounds.

<u>SPECIAL CONDITION 9</u>. There shall be no discharge of complexed metal bearing wastestreams and associated rinses from chemical metal cleaning unless this permit has been modified to include the new discharge.

SPECIAL CONDITION 10. Intake monitoring at Crawford Generating Station pursuant to Section 316(b) of the CWA was not required by USEPA in letters to Commonwealth Edison Company dated February 19, 1975 and June 1, 1976. It is determined that no intake monitoring or modification is being required by IEPA for reissuance of this NPDES Permit.

SPECIAL CONDITION 11. There shall be no discharge of collected debris from Outfall 001(d) Intake Screen Backwash.

DRAFT

Special Conditions

APR 1 1 1997

PUBLIC NOTICED

<u>PECIAL CONDITION 12</u>. The permittee shall record monitoring results on Discharge Monitoring Report Forms using one suce each discharge each month.

The completed Discharge Monitoring Report forms shall be submitted to IEPA no later than the 28th day of the following month, otherwise specified by the permitting authority.

Discharge Monitoring Reports shall be mailed to the IEPA at the following address:

Illinois Environmental Protection Agency Division of Water Pollution Control 2200 Churchill Road Post Office Box 19276 Springfield, Illinois 62794-9276

Attention: Compliance Assurance Section

5. ECIAL CONDITION 13. The upset provisions of 40 CFR 122.41(n) are hereby incorporated by reference.

<u>SPECIAL CONDITION 14</u>. The Agency may modify this permit during its term to incorporate biomonitoring requirements and additional limitations or requirements based on the biomonitoring results. Modifications under this condition shall follow public notice and opportunity for hearing.

CIAL CONDITION 15. A discharge limit of 0.05 mg/l (instantaneous maximum) shall be achieved for total residual oxidant when bromine biocides are used for condenser biofouling control, in accordance with Special Condition 4. Total residual oxidant shall be measured and reported in terms of total residual chlorine. Construction of treatment facilities which may be necessary to meet the limit for total residual oxidant may not be started until a construction permit has been issued by the Agency.

SPECIAL CONDITION 16. The Agency has determined that the effluent limitations in this permit constitute BAT/BCT for storm water which is treated in the existing treatment facilities for purposes of this permit reissuance, and no pollution prevention plan will be required for such storm water. In addition to the chemical specific monitoring required elsewhere in this permit, the permittee shall conduct an annual inspection of the facility site to identify areas contributing to a storm water discharge associated with industrial activity, and determine whether any facility modifications have occurred which result in previously-treated storm water discharges no longer receiving treatment. If any such discharges are identified the permittee shall request a modification of this permit within 30 days after the inspection. Records the annual inspection shall be retained by the permittee for the term of this permit and be made available to the Agency on request.

SPECIAL CONDITION 17. STORM WATER POLLUTION PREVENTION PLAN (SWPPP)

- A. A storm water pollution prevention plan shall be developed by the permittee for the storm water associated with industrial activity at this facility. The plan shall identify potential sources of pollution which may be expected to affect the quality of storm water discharges associated with the industrial activity at the facility. In addition, the plan shall describe and ensure the implementation of practices which are to be used to reduce the pollutants in storm water discharges associated with industrial activity at the facility and to assure compliance with the terms and conditions of this permit.
- B. The plan shall be completed within 180 days of the effective date of this permit. Plans shall provide for compliance with the terms of the plan within 365 days of the effective date of this permit. The owner or operator of the facility shall make a copy of the plan available to the Agency at any reasonable time upon request.
- C. The permittee may be notified by the Agency at any time that the plan does not meet the requirements of this condition. After such notification, the permittee shall make changes to the plan and shall submit a written certification that the requested changes have been made. Unless otherwise provided, the permittee shall have 30 days after such notification to make the changes.
- D. The discharger shall amend the plan whenever there is a change in construction, operation, or maintenance which may affect the discharge of significant quantities of pollutants to the waters of the State or if a facility inspection required by paragraph G of this condition indicates that an amendment is needed. The plan should also be amended if the discharger is in violation of any conditions of this permit, or has not achieved the general objective of controlling pollutants in storm water discharges. Amendments to the plan shall be made within the shortest reasonable period of time, and shall be provided to the Agency for review upon request.

Special Conditions

- E. The plan shall provide a description of potential sources which may be expected to add significant quantities of pollutants to storm water discharges, or which may result in non-storm water discharges from storm water outfalls at the facility. The plan shall include, at a minimum, the following items:
 - A topographic map extending one-quarter mile beyond the property boundaries of the facility, showing: the facility, surface water bodies, wells (including injection wells), seepage pits, infiltration ponds, and the discharge points where the facility's storm water discharges to a municipal storm drain system or other water body. The requirements of this paragraph may be included on the site map if appropriate.
 - 2. A site map showing:
 - The storm water conveyance and discharge structures;
 - ii. An outline of the storm water drainage areas for each storm water discharge point;
 - iii. Paved areas and buildings;
 - Areas used for outdoor manufacturing, storage, or disposal of significant materials, including activities that generate significant quantities of dust or particulates.
 - v. Location of existing storm water structural control measures (dikes, coverings, detention facilities, etc.);
 - vi. Surface water locations and/or municipal storm drain locations
 - vii. Areas of existing and potential soil erosion;
 - viii. Vehicle service areas;
 - ix. Material loading, unloading, and access areas.
 - 3. A narrative description of the following:
 - i. The nature of the industrial activities conducted at the site, including a description of significant materials that are treated, stored or disposed of in a manner to allow exposure to storm water;
 - Materials, equipment, and vehicle management practices employed to minimize contact of significant materials with storm water discharges;
 - Existing structural and non-structural control measures to reduce pollutants in storm water discharges;
 - Industrial storm water discharge treatment facilities;
 - v. Methods of onsite storage and disposal of significant materials;
 - 4. A list of the types of pollutants that have a reasonable potential to be present in storm water discharges in significant quantities.
 - 5. An estimate of the size of the facility in acres or square feet, and the percent of the facility that has impervious areas such as pavement or buildings.
 - 6. A summary of existing sampling data describing pollutants in storm water discharges.
- The plan shall describe the storm water management controls which will be implemented by the facility. The appropriate controls shall reflect identified existing and potential sources of pollutants at the facility. The description of the storm water management controls shall include:

DRAFT

Special Conditions

APR 1 1 199

- Storm Water Pollution Prevention Personnel Identification by job titles of the individuals who are responsible for developing, implementing, and revising the plan.
- Preventive Maintenance Procedures for inspection and maintenance of storm water conveyance system devices such as oil/water separators, catch basins, etc., and inspection and testing of plant equipment and systems that could fail and result in discharges of pollutants to storm water.
- Good Housekeeping Good housekeeping requires the maintenance of clean, orderly facility areas that discharge storm water.
 Material handling areas shall be inspected and cleaned to reduce the potential for pollutants to enter the storm water conveyance system.
- 4. Spill Prevention and Response Identification of areas where significant materials can spill into or otherwise enter the storm water conveyance systems and their accompanying drainage points. Specific material handling procedures, storage requirements, spill clean up equipment and procedures should be identified, as appropriate. Internal notification procedures for spills of significant materials should be established.
- 5. Storm Water Management Practices Storm water management practices are practices other than those which control the source of pollutants. They include measures such as installing oil and grit separators, diverting storm water into retention basins, etc. Based on assessment of the potential of various sources to contribute pollutants, measures to remove pollutants from storm water discharge shall be implemented. In developing the plan, the following management practices shall be considered:
 - Containment Storage within berms or other secondary containment devices to prevent leaks and spills from entering storm water runoff;
 - Oil & Grease Separation Oil/water separators, booms, skimmers or other methods to minimize oil contaminated storm water discharges;
 - Debris & Sediment Control Screens, booms, sediment ponds or other methods to reduce debris and sediment in storm water discharges;
 - iv. Waste Chemical Disposal Waste chemicals such as antifreeze, degreasers and used oils shall be recycled or disposed of in an approved manner and in a way which prevents them from entering storm water discharges.
 - Storm Water Diversion Storm water diversion away from materials manufacturing, storage and other areas of potential storm water contamination;
 - Covered Storage or Manufacturing Areas Covered fueling operations, materials manufacturing and storage areas to prevent contact with storm water.
- Sediment and Erosion Prevention The plan shall identify areas which due to topography, activities, or other factors, have a high potential for significant soil erosion and describe measures to limit erosion.
- 7. Employee Training Employee training programs shall inform personnel at all levels of responsibility of the components and goals of the storm water pollution control plan. Training should address topics such as spill response, good housekeeping and material management practices. The plan shall identify periodic dates for such training.
- Inspection Procedures Qualified plant personnel shall be identified to inspect designated equipment and plant areas. A tracking
 or follow-up procedure shall be used to ensure appropriate response has been taken in response to an inspection. Inspections
 and maintenance activities shall be documented and recorded.
- G. The permittee shall conduct an annual facility inspection to verify that all elements of the plan, including the site map, potential pollutant sources, and structural and non-structural controls to reduce pollutants in industrial storm water discharges are accurate. Observations that require a response and the appropriate response to the observation shall be retained as part of the plan. Records documenting significant observations made during the site inspection shall be submitted to the Agency in accordance with the reporting requirements of this permit.

Special Conditions

- H. This plan should briefly describe the appropriate elements of other program requirements, including Spill Prevention Control and Countermeasures (SPCC) plans required under Section 311 of the CWA and the regulations promulgated thereunder, and Best Management Programs under 40 CFR 125.100.
- The plan is considered a report that shall be available to the public under Section 308(b) of the CWA. The permittee may claim portions of the plan as confidential business information, including any portion describing facility security measures.
- J. The plan shall include the signature and title of the person responsible for preparation of the plan and include the date of initial preparation and each amendment thereto.

REPORTING

- K. The facility shall submit an annual inspection report to the Illinois Environmental Protection Agency. The report shall include results of the annual facility inspection which is required by Part G of the Storm Water Pollution Prevention Plan of this permit. The report shall also include documentation of any event (spill, treatment unit malfunction, etc.) which would require an inspection, results of the inspection, and any subsequent corrective maintenance activity. The report shall be completed and signed by the authorized facility employee(s) who conducted the inspection(s).
- L. The first report shall contain information gathered during the one year time period beginning with the effective date of coverage under this permit and shall be submitted no later than 60 days after this one year period has expired. Each subsequent report shall contain the previous year's information and shall be submitted no later than one year after the previous year's report was due.
- M. Annual inspection reports shall be mailed to the following address:

Illinois Environmental Protection Agency Division of Water Pollution Control Compliance Assurance Section Annual Inspection Report 2200 Churchill Road P.O. Box 19276 Springfield, Illinois 62794-9276

N. If the facility performs inspections more frequently than required by this permit, the results shall be included as additional information in the annual report.

SPECIAL CONDITION 18. In the event the permittee shall require the use of water tratment additives not previously used in the station's main condensors, the permittee shall request a modification in the permit in accordance with the standard conditions, Attachment H.

SPECIAL CONDITION 19. The use or operation of this facility shall be by or under the supervision of a Certified Class VARIABLEK operator.

ATTACHMENT H

Standard Conditions

Definitions

Act minos the Illinois Environmental Protection Act, Ch. 113, 172 III. Rev. Stat., Sec. 1001, 1052, as Amended.

Agency monte the thinois Environmental Protection Agency

Board means the Illinois Pollution Control Board

Clean Water Act (formerly referred to as the Federal Water Pollution Central Act) means 1:45-1-92-500, as amended 33 U.S.C. 1261 et seq.

NPDES Waternal Pollutant Discharge Elimination System) means the national program for record, modifying, revoking and religiously, terminating, monitoring and enforcing pretriatment requirements, under Societies 307, 402, 318 and 405 of the Clean Water Act.

USEPA masks the United States Environmental Protection Agency

Daily Discharge means the decharge of a pollutent measured during a calendar day or may 24-hour period that reasonably represents the calendar day for purposes of sampling for pollutents with limitations expressed in units of mass, the "daily discharge" is calculated as the total mass of the pollutent discharged over the day for pollutents with limitations expressed in other units of measurements, the "daily discharge" is calculated as the average measurement of the pollutent over the day.

Maximum Delty Olecherge Limitation Idealy maximum) moons the highest alloweble delty discharge

Average Monthly Discharge Limitation (30 day average) means the highest allowable average of daily discharges over a calendar month, calculated as the sum of all daily discharges measured during a calendar month divided by the number of daily discharges measured during that month.

Average Weekly Discharge Limitation 17 day average) means the highest allowable average of daily discharges over a calendar week, calculated as the sum of all daily discharges measured during a calendar week divided by the number of daily discharges measured during that week.

Beet Management Practices (BMPs) means achedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of waters of the State BMPs also include treatment requirements, operating procedures, and practices to control plent site runoff, spiflage or teaks, sludge or waste disposel, or drainage from raw material storage.

Allquot means a sample of specified volume used to make up a total composite sample

Grab Sample means an mitindual sample of at least 100 millihiters collected at a randomlyselected time over a period not exceeding 15 minutes.

24 Hour Composite Bernple meens a combination of at least 8 sample sixuorin of at least 100 militirers, collected at periodic intervals during the operating hours of a facility over a 24-hour period.

8 Hour Composite Sample means a combination of at least 3 sample aliquits of at least 100 millihitars, collected at periodic intervals during the operating hours of a facility over an 8 hour period.

Flow Proportional Composite Sample means a combination of sample aliquots of at least 100 m²/king collected at periodic mirrels such that after the time interval between each sheport or the values of each aliquot is proportional to either the stream flow at the time of sampling or the total stream flow since the collection of the previous aliquot.

- Duty to comply. The permittee must-comply with all conditions of this parent. Any permit noncompliance constitutes a violation of the Act and is grounds for enforcement action, permit termination, revocation and reissuance, modification, or for detail of a permit remained application. The permittee shall comply with effluent standards or prohibitions established under Section 30 f(a) of the Clean Water Act for toxic published within the time provided in the regulations that instablish those standards or prohibitions, even if the permit has not yet been modified to incorporate the requirement.
- (2) Duty to reapply if the permittee wishes to continue an activity regulated by this permit after the expension date of this permit, the permittee must apply for and obtain a new permit if the permittee submits a propin application as required by the Agency no later than 180 days prior to the expension date, this permit shall continue in full force and effect until the final Agency decision on the application has been made.
- (3) Need to half or reduce activity not a defence it shall not be a delense for a permutee in an enforcement action that it would have been recessary to holt or reduce the permuted activity in order to maintain compliance with the conditions of this permit.
- (4) Duty to mitigate The parmittee shall take all resourable steps to minimize or prevent any discharge in violation of this permit which has a reasonable likelihood of adversally affecting human health or the anyousmant.
- (5) Proper operation and meintenance. The permittee shall at all times properly operate and maintain all facilities and systems of breatment and control (and related appartenances) which are installed or used by the permittee to achieve compliance with the conditions of the permit Proper operation and maintenance includes effective performance, adequate timbing, adequate operator staffing and training, and adequate laboratory and process controls, including appropriate quality assurance princedures. This provision requires the operation of buck-up, or euxplicitions, or similar systems only when necessary to achieve compliance with the conditions of the permit.

- (6) Permit actions. This permit may be modified, revoked and raissued, or terminated for cause by the Agency pursuant to 40 CFR 122.62. The filling of a request by the permittee for a permit modification, revocation and relessance, or termination, or a notification of planned changes or enticipated noncompliance, does not stay any permit condition.
- Property rights. This purmit does not convey any property rights of any sort, or any exclusive privilege.
- (8) Duty to provide information. The permittee shell furnish to the Agency within a reasonable time, any information which the Agency may request to determine whether cause exists for modifying, revoking and releasing, or terminating this permit, or to determine compliance with the permit. The permittee shall also furnish to the Agency, upon request, copies of records required to be kept by this second.
- (9) Inspection and entry. The permittee shall allow an authorized representative of the Agency, upon the presentation of credentials and other documents as may be required by law, to
 - Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;
 - (b) Here access to end copy, at reasonable times, any records that must be kept under the conditions of this permit,
 - (c) Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
 - Idi Sample or monitor at resonable times, for the purpose of assuring permit compliance, or se otherwise authorized by the Act, any substances or parameters at any location.
- 110) Monitoring and records.
 - (a) Semplee and measurements taken for the purpose of monitoring shall be representative of the monitored activity.
 - (b) The permittee shell retain records of all monitoring information, including all celibration and maintenance records, and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least 3 years from the date of this permit, measurement, report or application. This period may be extended by request of the Agency at any time.
 - (c) Records of monitoring information shall include:
 - (1) The date, exact place, and time of sampling or measurements;
 - (2) The individual(s) who performed the sampling or measurements;
 - (3) The datelel analyses were performed;
 - (4) The individual(s) who performed the analyses;
 - (5) The analytical techniques or methods used; and
 - (6) The results of such analyses.
 - (d) Monitoring must be conducted according to test procedures approved under 40 CFR Part 136, unless other test procedures have been specified in this permit Where no test procedure under 40 CFR Part 136 has been approved, the permittee must submit to the Agency a test method for approved. The permittee shall calibrate and perform maintenance procedures on all monitoring and analytical instrumentation at intervals to ensure accuracy of measurements.
- (11) Signatory requirement. All applications, reports or information submitted to the Agency shall be signed and certified.
 - (a) Application All permit applications shall be signed as follows:
 - For a corporation by a principal executive officer of at least the level of vice president or a person or position having overall responsibility for environmental matters for the corporation;
 - (2) For a partnership or sole proprietership: by a general partner or the proprietor, respectively; or
 - (3) For a municipality, State, Federal, or other public agency: by either a principal executive officer or ranking elected official.
 - (b) Reports All reports required by permits, or other information requested by the Agency shall be signed by a person described in paregraph (a) or by a duly authorized representative of that person. A person is a duly authorized representative only if.
 - The authorization is made in writing by a person described in paragraph (a), and
 - (2) The authorization specifies either an individual or a position responsible for the overall operation of the facility, from which the discharge originates, such as a plant manager, superintendent or person of equivalent responsibility; and
 - (3) The written authorization is submitted to the Agency.

- (c) Changes of Authorization if an authorization under (b) is no longer accurate because a different individual or position has reaponability for the overall operation of the facility, a new authorization satisfying the requirements of (b) must be submitted to the Agency prior to or together with any reports, information, or applications to be signed by an authorized representative.
- (12) Reporting requirements.
 - (a) Ptenned changes. The permittee shall give notice to the Agency is soon as possible of any planned physical alterations or nikhtious to the permitted facility.
 - (b) Anticipated nencompliance The permittee shall give advance notice to the Agency of any plenned changes in the permitted facility or activity which may result in nencompliance with permit requirements.
 - (c) Compliance schedules. Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 14 days following each schedule date.
 - (d) Monitoring reports. Monitoring results shall be reported at the intervals specified elsewhere in this permit.
 - Monitoring results must be reported on a Discharge Monitoring Report (DMR).
 - (2) If the permittee monitors any pollutent more frequently then required by the permit, using test procedures approved under 40 CFR 136 or as specified in the permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR.
 - (3) Calculations for all limitations which require everaging of measurements shall utilize an enthmetic mean unless otherwise specified by the Agency in the permit
 - (e) Twenty-four hour reporting The permittee shall report any noncompliance which may endanger health or the environment Any information shall be provided orally within 24 bytes from the time the permittee becomes ewere of the circumstances. A written submission shall also be provided within 5 days of the time the permittee becomes aware of the circumstances. The written submission shall contain a description of the noncompliance and its cause, the period of noncompliance, including exact dates and times; and if the noncompliance has not have certained to radice, eliminate, and prevent reoccurrence of the noncompliance. The following shall be included as information which must be reported written 24 hours:
 - Any unanticipated bypass which exceeds any atthem tendatem in the permit;
 - (2) Violation of a maximum daily discharge Emilation for any of the pollutants listed by the Agency in the permit to be reported within 24 hours.

The Agency may waive the written report on a case by case basis if the oral report has been received within 24 hours.

- (f) Other noncompliance. The permittee shall report all instances of noncompliance not reported under paragraphs (17Hc), (d), or (a), at the time monitoring reports are submitted. The reports shall content the information listed in paragraph (12Ha).
- (g) Other information. Where the permittee becomes aware that it laided to submit any relevant facts in a permit application, or submitted occurrect information in a permit application, or is any report to the Agency, it shall promptly submit such facts or information.
- (13) Transfer of permits: A permit may be automatically transferred to a new permittee if:
 - The current permittee notifies the Agency at feast 30 days in intration of the proposed transfer date;
 - (b) The notice includes a written agreement between the existing and new permittees containing a specific data for transfer of permit responsibility, coverage and liability between the current and new permittees, and
 - (c) The Agency does not notify the existing permittee and the proposed new permittee of its intent to modify or revoke and ressue the parent if this notice is not received, the transfer is affective on the data specified in the agreement.
- (14) All manufacturing, commercial, mining, and silvicultural dischargers must notify the Agency as soon as they know or have reason to believe.
 - (a) That any activity has occurred or will occur which would result in the discharge of any toxic pollutant identified under Section 307 of the Clean Water Act which is not limited in the permit, if that discharge will exceed the highest of the following notification levels:
 - (1) One hundred micrograms per liter (100 ug/l);

- (2) I we hundred micrograms per liter (200 ug/f) for acrolein and acrylonatrie, five hundred micrograms per liter (500 ug/f) for 2,4clinitrophanol and for 2-methyl-4,6-deutrophanol, and one miligrem per liter (1 mg/f) for animony.
- (3) Live (5) times the maximum concentration value reported for that pollutent in the NPDES permit application, or
- (4) Ites level established by the Agency in this permit
- (b) Chat they have begun or expect to begin to use or manufacture as an intermediate or final product or byproduct any toxic pollutent which was not reported in the NPDES permit application.
- (15) All Publicly Owned Treatment Works (POTWs) must provide adequate note a to the Agency of the following
 - (a) Any new introduction of pollutents into that POTW from an indirect discharger which would be subject to Sections 301 or 306 of the Clean Water Act if it were directly discharging those pullutents, and
 - (b) Any substantial change in the volume or observoor of published being introduced into that POTW by a source introducing pollutants into the POTW at the time of issuance of the permit.
 - (c) For purposes of this paragraph, indequate cotes shall include infurnation on 6 this quality and quantity of efficient introduced into the POTW, and fall any additioned impact of the change us the quantity or quality of efficient to be declined from the POTW.
- (16) If the permit is exactly to a publicly owned or publicly regulated treatment works, the permittee shall require any understrail user of such treatment works to comply with laderel requirements concerning.
 - User charges pursuant to Section 704fbl of the Clean Water Act, and applicable regulations appearing in 40 CTR 35;
 - Lose pullatent of limit standards and proteintment standards pursuant to Section 307 of the Clase Water Act, and
 - (3) Inspection, monitoring and notry pursued to Section 308 of the Clean Water Act
- (17) If an applicable standard or londation is promulgated under Section 301(bH2)(C) and (O), 304(bH2), or 302(bH2) and that affloant standard or londation is more stringent than any influent londation in the period, or controls is pollutari not londed in the period, the period shall be promptly modified or revoked, and reissued to conform to that affloant standard or londation.
- (18) Any authorization to construct issued to the permittee pursuant to 35 fit Adm. Code 309 154 is hereby incorporated by reference as a condition of this purmit.
- 119) The paramter shall not croke any false statement, representation or cartification or any application, record, report, plan or other document submitted to the Agency or the USLPA, or required to be maintained under this percent.
- (20) The Clean Water Act provides that any person who violates a permit condition implementing Sections 301, 302, 305, 307, 308, 318, or 405 of the Clear Water Act is subject to a cred permit in excent \$10,000 per day of such violation. Any person who willfully or regulgarily violates permit conditions emplementing Sections 301, 302, 308, 307, or 308 of the Clear Water Act is subject to a fine of not less than \$2,500, nor more than \$25,000 per day of violation, or by impressumment for not prove than one year, or both.
- (21) The Claim Water Act provides that any parson who falsdess tempers with or knowingly renders inaccurate any monitoring device or method required to be maintained under period shall, upon conviction, be punished by a fine of not more than \$10,000 per violation, or by impreserment for not more than 6 inoutto, previolation, or by hold.
- 122) The Claim Water Act provides that any person who knowingly makes any false statement, representation, or certification in any record or other document submitted in required to be maintained under this permit shall, including manufacing reports or reports of compliance in non-compliance shall, upon conviction his pureshed by a fine of not more than \$10,000 per violation, or by imprisonment for not come than 0 months per violation, or by both.
- (23) Collected acreaning, sheries, shidges, and other solids shall be deposed of misuch a manuar as to prevent entry of those weaters for smoot from the westers into waters of the State. The proper authorization for such disposal shall be obtained from the Agency and is incorporated as part herset by reference.
- 12.4) In case of conflict featween these standard conditions and any other condition(s) included in this parint, the other condition(s) shall govern
- (25) The permittee shall comply with, in addition to the requirements of the permit, all applicable provisions of 35 ill Adm. Code, Subtitle C, Subtitle D, Subtitle F, and all applicable orders of the Board.
- (28) The provisions of this permit are severable, and if any provision of this permit, or the application of any provision of this permit is held invalid, the remaining provisions of this permit shall continue in full force and effect.